

OSBORN PENETRATING OIL 76202

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	OSBORN PENETRATING OIL 76202
Product Code	M-5711

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Lubricant
Uses Advised Against	None

Company Identification	Osborn 2350 Salisbury Road North Richmond, IN 47374 USA
------------------------	---

Telephone	(765) 965-5333
Fax	(765) 935-0212
E-Mail (competent person)	marketsupport@osborn.com

Emergency telephone number

Emergency Phone No.	Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)
---------------------	---

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 2; Liquefied gas; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1

Label elements

Hazard Symbol



DANGER

Signal word(s)

Hazard Statement(s)

Flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Precautionary Statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Wash hands and exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Avoid skin contact. Avoid breathing vapors.

Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.

Other hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

OSBORN PENETRATING OIL 76202

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Distillates (petroleum), hydrotreated heavy naphthenic	0 - 45	64742-52-5	Asp. Tox. 1; H304
Distillates (petroleum), hydrotreated light naphthenic	0 - 40	64742-53-6	Asp. Tox. 1; H304
Distillates (petroleum), hydrotreated light	20 - 30	64742-47-8	Flam. Liq. 4; H227 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 2; H401 Aquatic Chronic 2; H411
Butane	10 - 20	106-97-8	Flam. Gas 1; H220 Liquefied gas; H280
Propane	10 - 20	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
Anti-Corrosion Blend	0 - 5	Proprietary	Eye Irrit. 2; H319
Nonylphenol polyethylene glycol ether	< 1	127087-87-0	Acute Tox. 4 (oral; Inhalation); H302, H332 Eye Dam. 1; H318 Skin Irrit. 2; H315

Additional Information – None

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention. Get medical advice/attention if you feel unwell.

Skin Contact

Wash affected skin with soap and water. If irritation (redness, rash, blistering) develops, get medical attention. Take off contaminated clothing and wash it before reuse.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

Do not induce vomiting. Do not give anything by mouth to an unconscious person. Get immediate medical attention.

Most important symptoms and effects, both acute and delayed

Aspiration of droplets may cause pulmonary oedema.

Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

OSBORN PENETRATING OIL 76202

Special hazards arising from the substance or mixture

Pressurised container: May burst if heated

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Eliminate sources of ignition. Avoid contact with skin and eyes. Avoid breathing vapors.

Environmental precautions

Prevent liquid entering sewers, basements and work pits. Avoid release to the environment. Collect spillage.

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections

None

Additional Information

None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use product in a well-ventilated area only. Avoid contact with skin and eyes. Avoid breathing vapors.

Conditions for safe storage, including any incompatibilities

-Storage temperature

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

-Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

Specific end use(s)

Lubricant

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Mineral oils / Oil Mist	-----	5 mg/m3	5 mg/m3 ⁽¹⁾	-----	-----	⁽¹⁾ Inhalable
Alkanes (C9-C15)	-----	-----	1200 mg/m3	-----	-----	-----
Propane	74-98-6	1000 ppm	Aspyx. #	-----	-----	#

#Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

NIOSH 5026 (Oil mist; mineral); NIOSH 7300 (Elements by ICP); NIOSH 1501 (Hydrocarbons, Aromatic)

Exposure controls

Appropriate engineering controls

Ensure adequate ventilation.

Personal protection equipment

Eye/face protection

Wear protective eyewear (goggles, face shield, or safety glasses).



OSBORN PENETRATING OIL 76202

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber or Butyl rubber). Check with protective equipment manufacturer's data.

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Aerosol spray
Color.	Colorless
Odor	Petroleum spirit / Fuel oil-like
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-104 (Propane)
Evaporation Rate	Not available
Flammability (solid, gas)	Extremely flammable
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapor pressure (Pascal)	ca. 95×10^4 (Propane)
Vapor Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	450 (Propane)
Decomposition Temperature (°C)	Not available
Kinematic Viscosity	<20 cSt
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Other information	Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	This product should be stored away from sources of strong heat or oxidizing chemicals.
Hazardous decomposition product(s)	Carbon monoxide, Carbon dioxide, Acrid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

OSBORN PENETRATING OIL 76202

Hydrotreated Light Distillate (CAS No. 64742-47-8) - By analogy with similar materials:

Acute toxicity (calculated / estimated)	Oral: LD50 >5000 mg/kg-bw Dermal: LD50 >2000 mg/kg-bw Inhalation: LC0 ≥5.28 mg/l (Vapor), 4-hr. rat - May cause drowsiness or dizziness.
Irritation/Corrosivity	Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
Sensitization	It is not a skin sensitizer.
Repeated dose toxicity	Oral: NOEL 750 mg/kg Dermal: NOEL 0.5 ml/kg bw Inhalation: NOEL ≥1000 mg/m3
Carcinogenicity	It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity	Not to be expected
Reproductive toxicity	Not to be expected

Propane (CAS# 74-98-6):

Acute toxicity	Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)
Irritation/Corrosivity	No evidence of irritant effects from normal handling and use.
Sensitisation	It is not a skin sensitizer.
Repeated dose toxicity	NOEC: ≥19678 mg/m3 (28-day, rat, Systemic effects) LOEC: 21641 mg/m3 (28-day, rat, effects: Body weight)
Carcinogenicity	No data. It is unlikely to present a carcinogenic hazard to man.
Mutagenicity	There is no evidence of mutagenic potential.
Reproductive toxicity	None anticipated

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Hydrotreated Light Distillate (CAS No. 64742-47-8) - By analogy with similar materials:

Short term	LC50 (96 hour): 2.5 mg/L (fish) EC50 (48 hour): 1.4 mg/L (crustacea) EC50 (72 hour): 1.3 mg/L (algae)
Long Term	NOEC (28 days): 0.098 mg/L (fish) LOEC (21 days): 1.2 mg/L (crustacea) LOEL (72 hour): 1 mg/L (algae)
Persistence and degradability	Biodegradable
Bioaccumulative potential	The product has no potential for bioaccumulation.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
--------------------------------	--

OSBORN PENETRATING OIL 76202

SECTION 14: TRANSPORT INFORMATION

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None	-----	-----	-----

SARA 311/312 - Hazard Categories:

☒ Fire ☒ Sudden Release ☐ Reactivity ☒ Immediate (acute) ☐ Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
None	-----	-----

SARA 302 - Extremely Hazardous Substances (40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None	-----	-----

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: May 25, 2015

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H227: Combustible liquid.
- H280: Contains gas under pressure; may explode if heated.
- H302: Harmful if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H336: May cause drowsiness or dizziness.
- H401: Toxic to aquatic life.
- H411: Toxic to aquatic life with long lasting effects.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.